

Technical Specifications

High Wall FCU (with in-built motorized valve)

Unit Model		MKG-300	MKG-400	MKG-600	SUWX-24*
Cooling Capacity	kW	2.63	3.07	4.45	6.34
Heating Capacity (50C)	kW	3.69	4.33	6.3	8.53
Air Volume	CMH	510	680	1020	1140
Noise Level (H/M/L)	dB(A)	35/32/27	35/32/27	38/35/31	49/43/38
Power Input	W	40	44	60	59
Power Supply	V/Ph/Hz	220V / 1 Phase / 50Hz			
Thermostat Type		Wireless I.C. Remote Control			
Fan type		Cross-Flow Fan			
Water Flow Rate	m ³ /h	0.45	0.53	0.77	1.09
Pressure Drop	kPa	18	22	29	63
Inlet/Outlet connection dia.	mm	19	19	19	12.5
Drain	mm	19	19	19	16
Control Valve Diameter	mm	12.5	20	20	12.5
Net Dimensions(LxWxH)	mm	915x210x290	915x210x290	1070x210x315	1147x245x315
Net Weight	kg	12	12	15	15

Cooling capacity based on entering water temp. at 7°C and entering air temp. at 27°C DB / 19°C WB
 Heating capacity based on entering water temp. at 50°C and entering air temp. at 20°C DB
 Max inlet water temperature:75°C

* Not from Midea.